

# Desk/1500series

Interact with customers at the counter with the simplicity of a compact device



Speed up the payment for Desk/series terminals

Manage customer interface for any type of payment

Integrate with any counter space thanks to a compact and nimble design



The Desk/1500 can accept all traditional payment methods. Nimble in design, the Desk/1500 series takes up a limited space on a potentially busy countertop.

#### Optimized checkout time

Payment validation is better when synchronised with the customer and however they want to pay. Equipped with a clear contactless zone, large keypad and an advanced consumer display, the

Desk/1500 series enhances usability and accelerates the checkout.

#### Designed for a limited space

The compact Desk/1500 series fits easily on any counter, with options for either a mounted or unmounted terminal to suit the available desktop space. To save space, the Desk/1500 series can act in place of the larger Desk/5000 terminal.

#### Highest security

The Desk/1500 series is certified and fully compliant with the latest global and local PCI regulations to ensure long-term payment security compliance – protecting data for years to come.

#### Fast and unified integration

With plug-and-play installation and USB connection, the Desk/1500 series connects to any Desk/series device, offering a speedy and unified solution.



Desk/1500



DESK 1500			
Processor	• Application & Crypto processor	• Cortex A5	•
Memory	• Internal	• 128 MB Flash, 128 MB RAM	•
OS		• Telium TETRA	•
Card readers	• Magstripe • Smart card • Contactless	• ISO 1/2/3, 500K lifespan • EMV Level 1, 500K lifespan • EMV Level 1	• • •
Display	• Colour	• 2.8" display, QVGA (320x240 pixels)	•
Keypad		• 15 keys, raised marking, 4 function keys	•
Audio	• Buzzer		•
Terminal connections	• USB	• 1 USB Host	•

DESK 1500			
Terminal size		• 148x77x26 mm (5.8x3.03x1.02") • 180x83x43 mm (7.08x3.26x1.69")	N/A •
Weight		• 150 g (5.29 oz) • 254 g (8.95 oz)	N/A •
Environment	• Operating Temperature • Storage Temperature • Operating Humidity	• 0°C to +40°C (32°F to 104°F) • -20°C to +55°C (-4°F to 131°F) • 85% non-condensing at +40°C (104°F)	• • •
Accessory	• Privacy shield	• Factory mounted • Field upgradable	Option N/A
Security		• PCI PTS 5.x online & offline certified	•



www.ingenico.com

**ingenico**  
aWorldlinebrand